## S-912IV AUTOMATIC SCREEN PRINTER





If your screen printing work requires only a small-format printer, but you can't do without the automatic operation and precision of larger machines, the S-912M from A.W.T. / American M&M is the perfect choice.

Its adjustable elevated base allows the S-912M to accommodate substrates of varying thickness. And with the optional micro-adjustable table, the S-912M provides registration controls that ensure precise +/-.001" repeatability. Made in America, the unit is designed for reliable performance over the long term and easy maintenance.

When the time comes to equip your shop with an automatic small-format printer, choose the speed, precision, versatility, and durability of the S-912M by A.W.T. / American M&M. With its unique combination of features, the S-912M is easily the finest screen printer in its size and price range.


- In production for over 30 years
- Easy to operate plug in, set up and print
- Aircraft-quality aluminum table construction heaviest gauge printing surface
- State-of-the-art up-front controls
- Five-digit reset counter
- Micro-registration table available +/-.001"
- Variable cycle speeds
- Adjustable print stroke length
- Solid-state 1-15 second dwell timer
- Caster base for easy mobility
- Heavy-duty stainless-steel chassis frame

NEW! • Brushless, maintenance-free Quiet Vacuum





Elevated Base Lowers table away from screen for printing on plywood, glass, styrofoam, plastic extrusions or other thick substrates



Micro-Registration
Optional micro-adjustable table provides
rapid registry in .001" increments



Up-Front Control Panel
Provides easily accessible controls for operator
convenience and increased productivity



Quiet Vacuum Brushless, maintenance-free vacuum for quiet, efficient operation

## SPECIFICATIONS \_\_\_\_\_

VACUUM/PRINT AREA	9 x 12″ 55.9 x 76.2 cm
TABLE SIZE	18.5 x 20″
PRINT TABLE HEIGHT	38 - 40″
MAXIMUM SCREEN FRAME SIZE	18.5 x 20″
SPEED CYCLE	800 - 1,600 IPH
MACHINE DIMS (L x W x H)	38 x 21 x 52.5″
STANDARD ELECTRICAL	115 V/1 Ph/60 Hz-15 A 240 V/1 Ph/50 Hz-8 A
SHIPPING WEIGHT	375 lbs. (170 kg)

Electrical specifications available for all countries.

Our policy is one of continuous improvement. Therefore, we reserve the right to change specifications without prior notice.

© 2003 A.W.T. World Trade, Inc. No part of this literature may be reproduced without written permission. Specifications subject to change without notice. #LIT-1018 09/03

## STANDARD FEATURES

- Solid-state 1-15 second dwell timer
- 5-digit reset counter
- Adjustable print stroke
- Maximum screen frame 18.5 x 20"O.D.
- Caster base for easy mobility
- Aircraft-quality aluminum print bed
- 2"adjustable table height
- Brushless, maintenance-free Quiet Vacuum

## **OPTIONS**

- Micro-registration table
- Pneumatically-operated registration guides
- Front or rear pneumatic screen clamps
- Single-cycle foot switch
- Extra squeegee holders or floodbars
- Spare parts package
- Conversion to 50 Hz



A Division of The A.W.T. World Trade Group

Manufactured by

A.W.T. World Trade, Inc.

Corporate Headquarters: 4321 N. Knox Ave. Chicago, IL 60641-1906 USA 773.777.7100 • Fax: 773.777.0909 sales@awt-gpi.com • www.awt-gpi.com